



# City of Oroville

COMMUNITY DEVELOPMENT DEPARTMENT

Donald Rust  
DIRECTOR

1735 Montgomery Street  
Oroville, CA 95965-4897  
(530) 538-2425 FAX (530) 538-2426  
[www.cityoforoville.org](http://www.cityoforoville.org)

## Swimming Pool Safety Barrier Requirements

The intent of the swimming pool barrier requirements is to prevent uncontrolled access by children from a street or adjacent properties and from the home. The City of Oroville swimming pool requirements complies with the State Health and Safety Code Section 115920 to 115927, City of Oroville Code Title Section 6-2.5 and City of Oroville Ordinance #1747. Customers have the choice of the following A or B below when choosing a Pool Barrier.

- A. Fencing around property utilizing the house as part of a fence to prevent access to pool; Must meet the following requirements:
  - I. Fencing:
    - a. Minimum of 60" (inches) in height above the ground.
    - b. Opening between the ground and bottom of the fence is not more than 2" (inches).
    - c. Openings in the fence shall not allow passage of a sphere equal to or greater than 4" (inches).
    - d. An outside surface free of protrusions, cavities or other physical characteristics that would serve as handholds or footholds that could enable a child below the age of five years to climb over. Horizontal members shall be spaced at least 48" (inches) apart. Chain link may be used provided that the openings are not greater than 1- 3/4" (inches) measured horizontally.
  - II. Gate:
    - a. Minimum of 60" (inches) in height above the ground.
    - b. Access gates shall open away from the swimming pool.
    - c. Shall be a self-closing, self-latching with latching device to be a minimum of 60" (inches) above the ground.
  - III. Doors giving direct access to swimming pool area:
    - a. Shall be equipped with self-closing, self-latching device placed no lower than 54" (inches) above the floor or see Section IV (a) below.
    - b. Garage man door shall be considered as a gate; shall comply with Gate Requirements - See Section II above.
  - IV. Sliding doors giving direct access to swimming pool area:
    - a. Shall be equipped with audible alarm that a sound of sufficient volume to be heard throughout the dwelling. The alarm device shall be approved by the Chief Building Official.

V. Safety Pool Cover:

- a. Safety pool cover complying with American Society For Testing and Materials (ASTM - F1346-91) or approved by Chief Building Official may be used in lieu of alarm devices that are required for doors and sliding doors.

B. Fencing around pool only will meet the following requirements:

FENCING:

- a. Minimum of 60” (inches) above ground.
- b. Openings between the ground and bottom of fence is not more than 2” (inches)
- c. Openings in fence shall not allow passage of a sphere equal to or greater than 4” (inches).
- d. Access gates through the enclosure shall open away from the swimming pool and shall be self- latching device placed no lower than 60” (inches) above the ground.
- e. An outside surface free of protrusions, cavities or other physical characteristics that would serve as handholds or footholds that could enable a child below the age of five years to climb over. Horizontal members shall be spaced at least 48” (inches) apart. Chain link may be used provided that the openings are not greater than 1-3/4” (inches) measured horizontally.

The Requirement for a Barrier **DOES NOT** apply to any of the following:

- 1. Public swimming pools.
- 2. Hot tubs or spas with locking safety covers that comply with the American Society For Testing Materials – Emergency Performance Specification (ASTM - F1346-91)
- 3. An apartment complex or any residential setting other than a single-family home.

**I have read, understood and will comply with the pool barrier requirements under state and local law. If contractor is submitting for permit, property owner must still sign this form. A swimming pool permit will not be issued until this form is completed and returned to this office.**

Address: \_\_\_\_\_  
\_\_\_\_\_

Property owner:

\_\_\_\_\_  
Print Sign Date

Contractor:

\_\_\_\_\_  
Print Sign Date